



# T800-Ex FULLY RUGGED TABLET

- 8.1" HD LumiBond® 2.0 display for better viewing experience
- Getac proprietary SnapBack add-on featuring Smart card and contactless RFID reader Combo or 2nd expanded battery
- Choice of 1D/2D imager barcode reader, Serial port, Micro SD or Ethernet
- Up to 10 hours of battery life with one charge. LifeSupport™ battery swappable technology for uninterrupted battery life
- MIL-STD-810G and IP65 certified
- Enhanced Enterprise Security with optional Intel vPro, Windows Disk Encryption, TPM 2.0 and many more multi-factor authentication options.



SnapBack add-on



# Specifications

## Operating System

Windows 10 Pro

## Mobile Computing Platform

Platform Options:

Intel® Atom Processor x7-Z8750 1.6 GHz, burst up to 2.56 GHz  
- 2MB Cache

## VGA Controller

Intel® HD Graphics

## Display

8.1" IPS TFT LCD HD (1280 x 800)  
600 nits LumiBond® display with Getac sunlight readable technology

## Storage & Memory

4GB LPDDR3 expandable to 8GB  
Optional eMMC 64GB / 128GB

## Keyboard

6 tablet buttons (Windows, Power, Function Key, Camera Capture/ Barcode Reader Trigger, Volume Up, Volume Down)

## Pointing Device

Touchscreen

- Capacitive multi-touch screen
- Optional dual mode touchscreen (multi-touch and digitizer)

## Expansion Slot

Optional 1D/2D imager barcode reader

## I/O Interface

FHD webcam x 1  
8M pixels auto focus rear camera x 1  
USB 3.0 (9-pin) x 1  
Headphone out/Mic-in Combo x 1  
DC in Jack x 1  
Micro HDMI x 1

## Communication Interface

Intel® Dual Band Wireless-AC 7265, 802.11ac  
Bluetooth (v4.0)  
Optional dedicated GPS  
Optional 4G LTE mobile broadband

## Security Feature

TPM 2.0

## Power

AC adapter (65W, 100-240VAC, 50 / 60Hz)  
Li-Ion battery (7.4V, 4200mAh)

## Dimension (W x D x H) & Weight

227 x 151 x 24 mm (8.93" x 5.94" x 0.94")  
0.91kg (2 lbs)<sup>1</sup>

## Rugged Feature

MIL-STD-810G certified and IP65 certified  
6 feet drop resistant  
Vibration & drop resistant

## Environmental Specification

Temperature<sup>1</sup>:

- Operating: -21°C to 50°C / -5.8°F to 122°F
- Storage: -51°C to 71°C / -60°F to 160°F

Humidity:

- 95% RH, non-condensing

ATEX / IECEx zone 2/22

II 3G Ex ic IIC T4 Gc

II 3D Ex ic IIIB T130°C Dc

## Accessories

Main battery (7.4V, 4200mAh)  
2<sup>nd</sup> expanded battery (14.4V, 2100 mAh)  
AC adapter (65W, 100-240VAC)  
Capacitive stylus (Hard-tip)  
Digitizer pen

## Bumper-to-Bumper warranty

Accidents can take your equipment out of service when you least expect it, especially in a rugged environment, which can cause costly equipment downtime.

That is why Getac has introduced accidental damage as standard under our new Bumper-to-Bumper warranty, to help minimize your enterprise IT costs.

Bumper-to-Bumper is your hassle-free guarantee.

That means you can depend on us to have your unit back in service within days.

## Standard

3 years Bumper-to-Bumper.

- Battery life testing conducted under MobileMark 2007. Battery performance will vary upon software applications, wireless settings, power management settings, LCD brightness, customized modules and environmental conditions. The battery has a limited number of charge cycles and may eventually need to be replaced by a Getac service provider. Battery life and charge cycles vary by use and settings.
- Weight and dimensions vary from configurations and optional accessories.
- Tested by a national independent third party test lab following MIL-STD-810G.

# T800-Ex

## Fully Rugged Tablet



# Getac

## GETAC TECHNOLOGY CORPORATION

5F, Building A, No. 209, Section 1, Nangang Rd.,  
Nangang Dist., Taipei City, 11568, Taiwan, R.O.C.  
Tel : +886 2 2785 7888  
globalmarketing@getac.com | www.getac.com



Copyright © 2018 Getac Technology Corporation and/or any of its affiliates. All Rights Reserved.  
Information provided herewith is for reference only,  
available specification shall be subjected to quotation by request. V01M02Y18WW

# FIELDWORKS

Fieldworks Direct BV

Veemarktkade 8

NL-5222 AE 's-Hertogenbosch

e-mail: [info@fieldworks.nl](mailto:info@fieldworks.nl)

tel. +31(0) 73 624 1111

fax +31(0) 73 624 1112

[www.fieldworks.nl](http://www.fieldworks.nl)