



ZX70 FULLY RUGGED TABLET

- 7" LumiBond® Display with Getac Sunlight Readable Technology and Glove-enabled Capacitive Touchscreen
- 6 Feet Drop , MIL-STD-810G and IP67 Certified
- Optional Barcode Reader and RFID Reader
- Optional 4G LTE WWAN
- High Sensitivity GPS



Office Dock



Vehicle Dock



Specifications

Operating System

Android 6.0

Mobile Computing Platform

Platform Options:

Intel Atom® Processor x5-Z8350 1.44GHz, burst up to 1.92 GHz
- 2MB cache

VGA Controller

Intel® HD Graphics

Display

7" IPS TFT LCD HD (1280 x 720)

LumiBond® display with Getac sunlight readable technology

Capacitive touchscreen with glove on

Storage & Memory

2GB LPDDR3 expandable to 4GB

Optional eMMC 32GB / 64GB / 128GB

Keyboard

4 tablet buttons (Power, Barcode Launch Button, Volume Up, Volume Down)

Pointing Device

Touchscreen

- Capacitive multi-touch screen

Expansion Slot

MicroSD x1

I/O Interface

FHD webcam x 1

8M pixels auto focus rear camera x 1

MicroUSB 2.0 (Client) x 1

USB 2.0 (Host) x 1

Docking connector (Pogo/JAE)

DC in Jack x 1

Optional RF antenna pass-through for GPS and WWAN

Communication Interface

Wi-Fi 802.11n

Bluetooth (v4.0)

Dedicated GPS

Optional 4G LTE mobile broadband

Security Feature

Optional Contactless HF RFID/NFC combo readerⁱⁱ, ⁱⁱⁱ

Optional Barcode reader

Optional UHF RFID reader^{iv}, ^v

Power

AC adapter (24W, 100-240VAC, 50 / 60Hz)

Li-Ion battery (3.8V, 8400mAh)

Dimension (W x D x H) & Weight

218 x 142 x 27 mm (8.58 " x 5.6" x 1.08")

780g (1.71lbs)^{vi}

Rugged Feature

MIL-STD-810G certified and IP67 certified

6 feet drop resistant

Vibration & drop resistant

e-Mark certified for vehicle usage

Optional ANS/ISA 12.12.01

Environmental Specification

Temperature^{vii}:

- Operating: -21°C to 60°C / -6°F to 140°F

- Storage: -40°C to 71°C / -40°F to 160°F

Humidity:

- 95% RH, non-condensing

Accessories

Carry bag

AC adapter (24W; 12V/2A, 100-240VAC; 50 / 60 Hz)

Vehicle adapter (56W, 12-24VDC)

Capacitive stylus

Rotating Hand strap with Kick Stand and Stylus Holder

Office dock

Vehicle dock

USB to RS232 converter cable

Docking connector to HDMI converter cable

Protection film

Shoulder strap

Wrist strap

Bumper-to-Bumper warranty

Accidents can take your equipment out of service when you least expect it, especially in a rugged environment, which can cause costly equipment downtime.

That is why Getac has introduced accidental damage as standard under our new Bumper-to-Bumper warranty, to help minimize your enterprise IT costs.

Bumper-to-Bumper is your hassle-free guarantee.

That means you can depend on us to have your unit back in service within days.

Standard

3 years Bumper-to-Bumper.

- i Bluetooth performance and connectable distance may be subject to interference with the environments and performance on client devices, users may be able to reduce effects of interference by minimizing the number of active Bluetooth wireless devices that is operating in the area.
- ii 13.56MHz Contactless HF RFID/NFC reader (ISO 15693, 14443 A/B, Mifare and FeliCa™ compliant).
- iii HF RFID/NFC combo reader applies to US & EU
- iv UHF RFID reader is mutually exclusive with Barcode reader and HF RFID/NFC combo reader.
- v EU only (865~868MHz, UHF RFID tags of EPC Class 1 Gen2 ISO18000-6C standards compliant)
The maximum read distance of UHF RFID is determined by the design, size of individual tags and environments. Contacting local Getac Sales Representatives for test arrangements is highly recommended.
- vi Weight and dimensions vary from configurations and optional accessories.
- vii Tested by a national independent third party test lab following MIL-STD-810G.

ZX70

Fully Rugged Tablet



Docking Solutions

	Getac Office dock (JAE connector)	Getac Office dock (Pogo pin)	Getac Vehicle dock (JAE connector)	Getac Vehicle dock (Pogo pin)
USB Host	2	2	2	2
USB Client	1	--	--	--
HDMI	1	--	1	--
Audio Output	1	1	1	1
Speaker	--	--	1	1
LAN	1	1	1	1
RS232	--	--	1	1
DC in Jack	1	1	1	1
RF Pass through	--	--	2 (WWAN, GPS)	2 (WWAN, GPS)

Getac

GETAC TECHNOLOGY CORPORATION

5F, Building A, No. 209, Section 1, Nangang Rd.,
Nangang Dist., Taipei City, 11568, Taiwan, R.O.C.

Tel : +886 2 2785 7888

globalmarketing@getac.com | www.getac.com



Copyright © 2018 Getac Technology Corporation and/or any of its affiliates. All Rights Reserved.
Information provided herewith is for reference only,
available specification shall be subjected to quotation by request. V01M02Y18WW

FIELDWORKS

Fieldworks Direct BV

Veemarktkade 8

NL-5222 AE 's-Hertogenbosch

e-mail: info@fieldworks.nl

tel. +31(0) 73 624 1111

fax +31(0) 73 624 1112

www.fieldworks.nl