2621 Ridgepoint Drive, Suite 235 Austin, TX 78754

800.866.6506 (US)

www.ikey.com

DBL-81

iKey

Backlit Keyboard in Stainless Steel Case

The DBL-81 is a small-footprint keyboard that offers an alternative solution when space is at a premium. Built in an industrial strength stainless steel bezel, the DBL-81 features red LED backlighting for use in low-light environments. It has 12 function keys and standard keycap sizing. The DBL-81 is designed to meet NEMA 4X specifications for protection in harsh environments from dirt, dust, debris and liquids.



Technical Specifications	
Certifications	NEMA 4X, CE UL60950, FCC Part 15 Class B
Shock	3x11 ms pulses of 50g on each of 3 axes
Cable	LENGTH: 10 feet (3.048 meters) DESIGN: PS/2, AT or Single-Cable USB
Key Switch	MATERIAL: Industrial silicone rubber LIFE: 10 million cycles TRAVEL: 0.055 in. (1.4 mm) ACTUATION FORCE: 180g (+/- 30g) FEEDBACK: Tactile with mechanical snap
Vibration	POWER SPECTRAL DENSITY: 0.04g/Hz FREQUENCY RANGE: 20Hz - 2 kHz DURATION OF TEST PER AXIS: 3 hours
Power	PS/2: 200 mA@5V (from Keyboard port) USB: 200 mA@5V (from CPU port)
Flammability	PRINTED CIRCUIT BOARD: 94 VO SILICONE OVERLAY: 94 HB INTERFACE CABLE: 94 VO
Compatability	PS/2: All Windows Operating Systems USB: All Windows and Macintosh OS
Temperature Range	STORAGE: -40C to +90C (-40F to +194F) OPERATING: -40C to +70C (-40F to +158F)
Weight	4.25 lbs (1.02 kg)
Warranty	1 year limited warranty
Humidity	100%
Dimensions	13.25" x 6.94" x 1.75" (w-h-d) 336.6mm x 176.3mm x 44.5mm
Model Numbers	
Features and Benefits	
Red Backlit Keys	Stainless Steel Case
• LISP DS/2 and AT Configurations Available	

• USB, PS/2 and AT Configurations Available

©2011 iKey, Ltd. All rights reserved. 2621 Ridgepoint Drive Suite 235 Austin, TX 78754 1-800-866-6506 (US) +1-512-837-0283 (international)