

DP-860-OEM

Compact Industrial OEM Keyboard

The small-footprint DP-860-OEM is built for versatility and convenience, making it ideal for mobile applications and space saving. In addition, its integrated HulaPoint II™ pointing device eliminates the need for an external mouse. The DP-860-OEM meets NEMA 4X specifications when properly installed.



Technical Specifications

Certifications	NEMA 4X UL60950, FCC Part 15 Class B
Shock	3x11 ms pulses of 50g on each of 3 axes
Cable	LENGTH: 10 feet (3 meters) DESIGN: "Y" PS/2 (providing separate keyboard and mouse connections), or Single-Cable USB
Key Switch	MATERIAL: Industrial silicone rubber LIFE: 10 million cycles TRAVEL: 0.055 ACTUATION FORCE: 200g (+/- 20g) FEEDBACK: Tactile with mechanical snap
Vibration	POWER SPECTRAL DENSITY: 0.04g/Hz FREQUENCY RANGE: 20Hz - 2kHz DURATION OF TEST PER AXIS: 3 hours
Power	PS2: KEYBOARD: 50mA@5V (Keyboard port) HULAPOINT: 35mA@5V (Mouse port) USB: 85mA@5V (CPU port)
Flammability	PRINTED CIRCUIT BOARD: 94 VO SILICONE OVERLAY: 94HB INTERFACE: 94 VO
Compatability	PS/2 KEYBOARD/HULPOINT: All Windows Operating Systems USB KEYBOARD/HULAPOINT: All Windows and Macintosh OS
Temperature Range	STORAGE: -40C to +70C OPERATING: -20C to +60C
Weight	1 lb (0.45 kg)
Warranty	90 day limited warranty
Humidity	100% (when properly installed)
Dimensions	11.12" x 6.05" x 0.42" (w-h-d) 282.5mm x 153.7mm x 10.7mm
Model Numbers	

Features and Benefits

- 84-Key Functionality
- Integrated HulaPoint II Pointing Device
- OEM Kit: PCB, rubber overlay, and cable