

# DP-88-OEM

## Compact Industrial OEM Keyboard

The DP-88-OEM is a small-footprint keyboard that meets harsh use standards. It has 88 full-size keys with embedded notebook key functions. The DP-88-OEM is a perfect fit for industrial, kiosk or mobile computing needs. It is designed to meet NEMA 4X specifications when properly installed.



### Technical Specifications

|                   |   |
|-------------------|---|
| Certifications    | NEMA 4X UL60950, FCC Part 15 Class B  |
| Shock             | 3x11 ms pulses of 50g on each of 3 axes   |
| Cable             | LENGTH: 4 ft coiled (1.2m)  |
| Key Switch        | MATERIAL: Industrial silicone rubber LIFE: 10 million cycles TRAVEL: 0.055 ACTUATION FORCE: 200g (+/- 20g) FEEDBACK: Tactile with mechanical snap |
| Vibration         | POWER SPECTRAL DENSITY: 0.04g/Hz FREQUENCY RANGE: 20Hz - 2 kHz DURATION OF TEST PER AXIS: 3 hours   |
| Power             | PS2: KEYBOARD: 50mA@5V (from Keyboard port) USB: 50mA@5V (from Keyboard port)   |
| Flammability      | PRINTED CIRCUIT BOARD: 94 VO SILICONE OVERLAY: 94HB   |
| Compatability     | PS/2 KEYBOARD: All Windows Operating Systems USB KEYBOARD: All Windows and Macintosh OS   |
| Temperature Range | STORAGE: -40C to +90C OPERATING: -40C to +70C   |
| Weight            | 1 lb (0.45 kg)  |
| Warranty          | 90 day limited warranty   |
| Humidity          | 100% (when properly installed)  |
| Dimensions        | 11.12" x 6.05" x 0.42" (w-h-d) 282.45mm x 153.67mm x 10.7mm   |