

2621 Ridgepoint Drive, Suite 235 Austin, TX 78754

## 800.866.6506 (US)

www.ikey.com

# DT-5K

## Keyboard with Integrated HulaPoint II™

The DT-5K combines HulaPoint II™ an upgraded pointing device that offers i mproved sensitivity and increased durability, with a 10-key numeric keypad in a ruggedized stainless steel case, providing dual functionality in one compact unit. Its 20 function keys provide user versatility. This keyboard also offers user Windows keys for ease of access to the operating system.



### **Technical Specifications**

Certifications NEMA 4X UL60950, FCC Part 15 Class B
Shock 3x11 ms pulses of 50g on each of 3 axes

Cable LENGTH: 10 feet (3 meters) DESIGN: "Y" PS/2 Cable (providing separate keyboard and mouse connections), or Single-

Cable USB

Key Switch MATERIAL: Industrial silicone rubber LIFE: 10 million cycles TRAVEL: 0.055 in. (1.4 mm) ACTUATION FORCE: 7.03 oz

+/- 1.06 oz (200g +/- 20g) FEEDBACK: Tactile with mechanical snap

Vibration POWER SPECTRAL DENSITY: 0.04g/Hz FREQUENCY RANGE: 20Hz - 2 kHz DURATION OF TEST PER AXIS: 3

hours

Power PS/2 or AT/Serial: KEYBOARD: 50mA@5V (from Keyboard port) HULAPOINT: 35mA@5V (from Mouse port) USB:

85mA@5V (from CPU port)

Flammability PRINTED CIRCUIT BOARD: 94 VO SILICONE OVERLAY: 94 HB INTERFACE CABLE: 94 VO

Compatability PS/2 KEYBOARD/HULAPOINT: All Windows Operating Systems USB KEYBOARD/HULAPOINT: All Windows and

Macintosh OS

Temperature Range STORAGE: -40C to +70C (-40F to +158F) OPERATING: -20C to +60C (-4F to +140F)

Weight 5.25 lbs +/- 0.10 lbs (2.38 kg +/- 0.05 kg)

Warranty 1 year limited warranty

Humidity 100%

Dimensions 16.25" x 7.88" x 1.80" (w-h-d) 412.8mm x 200.2mm x 45.7mm

Model Numbers

### **Features and Benefits**

10-Key Numeric Pad
 113-Key Functionality

20 Function Keys
 Integrated HulaPoint II Pointing Device

• USB, PS/2 and AT Configurations Available