

# DT-810-TB

## Keyboard with Integrated Trackball



The DT-810-TB is constructed using a highly rugged, stainless steel case and industrial silicone rubber pad. The DT-810-TB's trackball pointing device is a completely sealed 25-mm unit. The trackball is operated using sealed stainless steel switches with left, right and middle click functions.

### Technical Specifications

Certifications	NEMA 4X
Shock	3x11 ms pulses of 50g on each of 3 axes
Cable	LENGTH: 10 feet (3 meters) DESIGN: "Y" PS/2 Cable (providing separate keyboard and mouse connections), or USB cable
Key Switch	MATERIAL: Industrial silicone rubber LIFE: Greater Than 10 Million Cycles TRAVEL: 0.055 in. (1.4mm) ACTUATION FORCE: 7.05 oz +/- 1.06 oz (200g +/- 30g) FEEDBACK: Tactile with mechanical snap
Vibration	POWER SPECTRAL DENSITY: 0.04g/Hz FREQUENCY RANGE: 20Hz - 2 kHz DURATION OF TEST PER AXIS: 3 hours
Power	PS2: KEYBOARD: 50mA@5V (from Keyboard port) TRACKBALL: 20mA@5V (from Mouse port) USB: 70mA@5V (from CPU port)
Compatibility	PS/2 KEYBOARD/TRACKBALL: All Windows Operating Systems USB KEYBOARD/TRACKBALL: All Windows and Macintosh OS
Temperature Range	STORAGE: -40C to +85C (-40F to +185F) OPERATING: 0C to +65C (+32F to +149F)
Weight	4.00 lbs +/- 0.10 lbs (1.81 kg +/- 0.05 kg)
Warranty	1 year limited warranty
Humidity	100%
Dimensions	14.80" x 5.72" x 1.69" (w-h-d) 376mm x 144.3mm x 42.9mm
Model Numbers	

### Features and Benefits

- 12 Function Keys
- PS/2 or USB configurations available
- PS/2
- Trackball
- Industrial
- NumLock Access
- Integrated Trackball
- Silicone Rubber
- USB
- Desktop
- Stainless Steel