

2621 Ridgepoint Drive, Suite 235 Austin, TX 78754

800.866.6506 (US)

www.ikey.com

## **DU-1000**

## **Keyboard with Polycarbonate Case**

The DU-1000 features the convenience of a full numeric keypad and a lightweight polycarbonate case. Suitable for 19-inch rack applications, the DU-1000 offers 104-key functionality and USB compatibility. It has 12 function keys as well as mounting holes in case.



## **Technical Specifications**

Certifications NEMA 4X UL60950, FCC Part 15 Class B

Shock 3x11 ms pulses of 50g on each of 3 axes

Cable LENGTH: 10 feet (3 meters) DESIGN: PS/2 or Single-Cable USB

Key Switch MATERIAL: Industrial silicone rubber LIFE: 10 million cycles TRAVEL: 0.055 in. (1.4mm) ACTUATION FORCE: 6.35

oz. +/- 1.06 oz. (180g +/- 30g) FEEDBACK: Tactile with mechanical snap

Vibration POWER SPECTRAL DENSITY: 0.04g/Hz FREQUENCY RANGE: 20Hz - 2 kHz DURATION OF TEST PER AXIS: 3

hours

Power PS/2 or AT/Serial: 50mA@5V (from Keyboard port) USB: 50mA@5V (from CPU port)

Flammability PRINTED CIRCUIT BOARD: 94 VO SILICONE OVERLAY: 94 HB INTERFACE CABLE: 94 VO

Compatability PS/2: All Windows Operating Systems USB: All Windows and Macintosh OS

Temperature Range STORAGE: -40C to +90C (-40F to +194F) OPERATING: -40C to +70C (-40F to +158F)

Weight 2.25 lbs +/- 0.10 lbs (1.02 kg +/- 0.05 kg)

Warranty 1 year limited warranty

Humidity 100%

Dimensions 14.94" x 6.63" x 1.81" (w-h-d) 379.5mm x 168.4mm x 45.9mm

Model Numbers

## **Features and Benefits**

• 10-Key Numeric Pad 
• 104-Key Functionality

Polycarbonate Case with Mounting Holes
 PS/2 or USB configurations available