

DURABOOK

Prepared for the Unexpected



Introducing the DURABOOK Rugged Product Lineup

FOR THE MOST EXTREME AND HAZARDOUS ENVIRONMENTS.

Some environments require rugged products that can literally take a beating. When you need mobile computing solutions they can depend on in extreme environments, rugged is a must. Getting durability, performance and reliability in any environment and any condition is crucial. Built to meet the heightened needs of industry clients, DURABOOK's unmatched rugged product lineup has everything you need.

RUGGED FOR THE REAL WORLD.



DURABOOK INNOVATION. RUGGED DOMINATION.



Certified by independent third-parties for MIL-STD-810G and IP ratings, as well as ANSI/ISA 12.12.01 and MIL-STD-416G/416F.



Survived drop tests up to 6 feet (182 cm), rigorous vibration and impact protection tests.



Experience peak performance in extreme temperatures, whether in freezing cold up to -30°C or extreme hot temperatures of 60°C.




DynaVue® technology improves display clarity and 23% wider viewing angle, while the screen is designed and built at industrial class for outdoor weather and light conditions.



Leading rugged design to increase productivity and efficiency for any conditions.



Unsurpassed thermal solution for continuous work in mission-critical situations.



Designed from the ground up with high-performance materials for full protection.



Webcams with physical privacy shutters for additional protection, opened and closed with just one simple finger movement.

DURABOOK

DURABOOK is the core brand by Twinhead International Corporation. In 2000, the company manufactured its first military-grade rugged laptop, followed by the introduction of the DURABOOK brand in 2002. The DURABOOK line quickly expanded to meet the demands of customers in a broad range of markets that require rugged mobile solutions.

Today, rugged DURABOOK devices have a loyal customer base around the globe, including most branches of the U.S. Armed Forces, public safety agencies, numerous field service organizations, as well as companies that specialize in oil & gas, logistics, healthcare, utilities and automotive industries.

INNOVATION COMMITMENT SATISFACTION

From its founding in 1984, Twinhead International Corporation, now a public Taiwan company, has been a major supplier of computing devices for more than 35 years with commitment on developing products and solutions for the computer industry.

Innovative driven with great engineering capability, strict production quality control and uncompromising customer-oriented services, Twinhead business covers mobile systems, tactical solutions, peripherals and industrial oriented PCs and displays.

WE ARE GLOBAL.



AT THE FIELD.

GENERAL SPECS & PERFORMANCE FEATURES



Z14I Laptop



S14I Laptop



S15AB Laptop



U11I Tablet



R11 Tablet



R11L Tablet

Operating System	Windows® 10 Pro 64-bit	Windows® 10 Pro 64-bit	Windows® 10 Pro 64-bit	Windows® 10 Pro 64-bit	Windows® 10 Pro 64-bit	Windows® 10 Pro 64-bit
Processor	Intel® Core™ i5-8250U (i7 optional)	Intel® Core™ i5-8250U (i7 / i3 optional)	Intel® Core™ i5-8265U (i7 optional)	Intel® Core™ i5-10210Y (i7 optional)	Intel® Core™ i5-8250U (i7 optional)	Intel® Pentium® 4417U
Graphics	Intel® UHD Graphics 620 Optional NVIDIA® GeForce® GTX1050	Intel® UHD Graphics 620 Optional NVIDIA® GeForce® GTX1050 ³	Intel® UHD Graphics 620	Intel® UHD Graphics	Intel® UHD Graphics 620	Intel® HD Graphics 610
Memory	8-32 GB (2400MHz DDR4)	4-32 GB (2400MHz DDR4)	8-16 GB (2400MHz DDR4)	8-16 GB (1866MHz DDR3)	8-16 GB (2400MHz DDR4)	4 GB (2400MHz DDR4)
Storage	256 GB SSD Optional OPAL 2.0 SSD Optional 2nd SSD	256 GB SSD Optional OPAL 2.0 SSD Optional 2nd SSD ³	256 GB SSD	128 GB SSD Optional OPAL 2.0 SSD	128 GB SSD	64 GB SSD
Display	14.0” FHD (1920 x 1080) with 1000 nits DynaVue® Technology	14.0” FHD (1920 x 1080) Optional with 1000 nits DynaVue® Technology	15.6” FHD (1920 x 1080) Optional with 500 nits	11.6” FHD (1920 x 1080) Optional with 1000 nits DynaVue® Technology	11.6” FHD (1920 x 1080) Optional with 500 nits DynaVue® Technology	11.6” FHD (1920 x 1080) Optional with 500 nits DynaVue® Technology
Touchscreen	Multi-Touch	Multi-Touch		Multi-Touch optional with digitizer	Multi-Touch	Multi-Touch
Camera	2.0 MP with shutter design	Optional 2.0 MP with shutter design & integrated microphone	2.0 MP	Front : 2.0 MP Rear : Optional 8.0 MP with auto-focus and flash	Front : 2.0 MP Rear : 5.0 MP with auto-focus and flash	Front : 2.0 MP Rear : 5.0 MP with auto-focus and flash
Additional Key Buttons	2 (user-definable)	2 (user-definable)		5 (2 user-definable)	6 (1 user-definable)	6 (1 user-definable)
Security	Intel® vPro™ Technology TPM 2.0 Easy removable SSD Smart card reader default Stealth mode Night vision mode Optional fingerprint scanner Optional RFID reader	Intel® vPro™ Technology TPM 2.0 Easy removable SSD Stealth mode Optional smart card reader ¹² Optional night vision mode ¹⁰ Optional fingerprint scanner Optional RFID reader ¹²	TPM 2.0 Smart card reader default ¹² Optional RFID reader ¹²	Intel® vPro™ Technology TPM 2.0 Easy removable SSD Stealth mode Optional smart card reader × 1 or × 2 ⁹ Optional night vision mode ¹⁰ Optional fingerprint scanner Optional RFID reader ⁹	Intel® vPro™ Technology TPM 2.0 Stealth mode Optional smart card reader Optional RFID reader	TPM 2.0 Stealth mode Optional smart card reader Optional RFID reader
I/O Interfaces	USB 3.1 (type A) × 2 • USB 3.1 (type C) × 1 USB 2.0 (type A) × 1 Audio in/out × 1 RJ45 × 2 • Serial port × 2 DP port × 1 • HDMI port × 1 • VGA port × 1 Docking connector × 1 SIM card × 1 • microSD card (microSDXC) × 1 Smart card reader × 1 PCMCIA Type II × 1 Express Card 54 × 1 or PCMCIA Type II × 1 DC-In × 1	USB 3.1 (type A) × 2 USB 2.0 (type A) × 2 Audio in/out × 1 RJ45 × 1 HDMI port × 1 • VGA port × 1 ³ Serial port × 1 (optional to support RS422 / RS485) Optional docking connector × 1 SIM card × 1 • SD card (SDXC) × 1 Optional smart card reader × 1 ¹² DC-In × 1	USB 3.1 Gen 1 (type A) × 2 USB 3.1 Gen 2 (type A) × 1 USB 3.1 (type C) × 1 Audio in/out × 1 RJ45 × 1 Serial port × 1 HDMI port × 1 • VGA port × 1 SIM card × 1 SD card (SDXC) × 1 Smart card reader × 1 DC-In × 1	USB 3.1 (type A) × 1 2nd USB 3.1 (type A) × 1 ⁸ Audio in/out × 1 microSD card (microSDHC, microSDXC) × 1 RJ45 × 1 SIM card × 1 HDMI port × 1 Docking connector × 1 Optional smart card reader × 1 or × 2 ⁹ DC-In × 1	USB 3.0 (type A) × 2 Audio in/out × 1 microSD card (microSDXC) × 1 Docking connector × 1 SIM card × 1 DC-In × 1	USB 3.0 (type A) × 2 Audio in/out × 1 microSD card (microSDXC) × 1 Docking connector × 1 SIM card × 1 DC-In × 1
Wireless Connectivity	AC 9260 / Bluetooth® V5.0 Optional dedicated GPS & 4G LTE	AC 9260 / Bluetooth® V5.0 Optional dedicated GPS & 4G LTE ³	AC 9260 / Bluetooth® V5.0 Optional GPS & 4G LTE (combo)	AC 9260 / Bluetooth® V5.0 Optional dedicated GPS & 4G LTE	AC 9260 / Bluetooth® V5.0 Optional dedicated GPS ⁶ Optional GPS & 4G LTE (combo)	AC 9260 / Bluetooth® V5.0 Optional dedicated GPS ⁶ Optional GPS & 4G LTE (combo)
Media Bay / Expansion Slot	Optional DVD super multi Optional 2nd battery Optional 2nd storage Optional PCI-Express 2.0 (2 slots) ¹³ Optional discrete VGA ¹³	Optional DVD super multi Optional 2nd battery ³ Optional 2nd storage ³ Optional ExpressCard 54 × 1 and PCMCIA Type II × 1 ³ Optional PCMCIA Type II × 2 ³	DVD super multi Optional 2nd SSD Optional 2nd SSD & 3rd SSD ¹¹	Optional serial port (RS232, 422 and 485 : D-sub,9-pin) or 2nd USB 3.1 (type A) or 1D/2D barcode reader ⁸ Optional PCMCIA Type II, ExpressCard 54 or RFID or 2nd smart card reader ⁹	Optional 1D/2D barcode reader Optional RJ45 port, smart card reader or RFID ⁷	Optional 1D/2D barcode reader Optional RJ45 port, smart card reader or RFID ⁷
Power Adapter	AC adapter : 100-240V, 50Hz-60Hz, 90W Optional AC adapter (100-240V, 50Hz-60Hz, 120W), with NVIDIA® VGA	AC adapter : 100-240V, 50Hz-60Hz, 65W Optional AC adapter (100-240V, 50Hz-60Hz, 120W), with NVIDIA® VGA ³	AC adapter : 100-240V, 50Hz-60Hz, 65W	AC adapter : 100-240V, 50Hz-60Hz, 65W	AC adapter : 100-240V, 50Hz-60Hz, 65W	AC adapter : 100-240V, 50Hz-60Hz, 65W
Battery Life ¹	16 (up to 25 hours with optional 2nd battery)	12 (up to 24 hours with optional 2nd battery)	13.5	13.5 (up to 24 hours with optional hi-cap battery)	8 (up to 16 hours with optional hi-cap battery)	8 (up to 16 hours with optional hi-cap battery)
Hot-Swappable Battery	Optional	Optional		Optional		
Operating Temperature	-20°C ~ 60°C / - 4°F ~ 140°F	-20°C ~ 60°C / - 4°F ~ 140°F	-20°C ~ 60°C / - 4°F ~ 140°F	-20°C ~ 60°C / - 4°F ~ 140°F	-20°C ~ 60°C / - 4°F ~ 140°F	-20°C ~ 60°C
Storage Temperature	-51°C ~ 71°C / -60°F ~ 160°F	-51°C ~ 71°C / -60°F ~ 160°F	-51°C ~ 71°C / -60°F ~ 160°F	-46°C ~ 71°C / -51°F ~ 160°F	-40°C ~ 71°C / -40°F ~ 160°F	-40°C ~ 71°C / -40°F ~ 160°F
Dimension	356 mm (L) × 280 mm (W) × 50 mm (H) ⁴ 14.02” (W) × 11.02” (D) × 1.97” (H) ⁴	350 mm (L) × 282 mm (W) × 38 mm (H) ⁴ 13.78” (W) × 11.1” (D) × 1.49” (H) ⁴	375 mm (L) × 273 mm (W) × 29.5 mm (H) 14.76” (W) × 10.75” (D) × 1.16” (H)	317mm (W) × 215mm (D) × 24 mm (H) 12.48” (W) × 8.46” (D) × 0.94” (H)	298 mm (L) × 192 mm (W) × 20 mm (H) 11.73”(L) × 7.56” (W) × 0.78” (H)	298 mm (L) × 192 mm (W) × 20 mm (H) 11.73”(L) × 7.56” (W) × 0.78” (H)
Weight ⁵	3.6 kg / 7.94 lb	2.3 kg / 5.07 lb	2.6 kg / 5.9 lb	1.39 kg / 3.06 lb	1.2 kg / 2.7 lb	1.2 kg / 2.7 lb

RUGGED FEATURES

MIL-STD-810G Certified ²	●	●	●	●	●	●
MIL-STD-461G / 461F Certified ²	461G			461G	461F	461F
Drop Rating / IP Certified ²	6 ft / IP 65	4 ft / IP 53	3 ft / IP 5X	6 ft / IP 65	4 ft / IP 65	4 ft / IP 65
ANSI/ISA 12.12.01	●			●	●	●
Removable Quick-Release Storage	●	●		●		
Aluminum-Magnesium Alloy Chassis	●	●	●	●	●	●
Fanless Design	●			●		
3-Year Warranty	●	●	●	●	●	●

1. Battery life, unless otherwise stated, is based on MobileMark. Results may vary under different situations including hardware configuration, software, operating conditions, power management settings and other factors.

2. Tested by a national, independent third-party lab following MIL-STD-810G, MIL-STD-461G, MIL-STD-461F and IEC 60529 standards.

3. Not available in combination with Intel® Core™ i3-8130U.

4. Actual height may vary with optional discrete VGA.

5. Actual weight may vary with different configurations.

6. GPS and WWAN are mutually exclusive options.

7. RJ45, smart card reader and RFID are mutually exclusive options.

8. 2nd USB 3.1 type A port, RS232 or 1D/2D barcode reader are mutually exclusive options. USB 2.0 or USB 3.1 type C are also available as

project-based features.

9. PCMCIA Type II, ExpressCard 54, RFID and 2nd smart card reader are mutually exclusive options.

10. Night vision mode is available only for sunlight readable display.

11. Factory option only. Support RAID 0 and RAID 1.

12. RFID and smart card reader are mutually exclusive.

13. PCI-Express 2.0 and discrete VGA are mutual exclusive options.



Fieldworks Direct BV
Veemarktkade 8
NL-5222 AE 's-Hertogenbosch

e-mail: info@fieldworks.nl
tel. +31(0) 73 624 1111
fax +31(0) 73 624 1112

www.fieldworks.nl

DURABOOK

Prepared for the Unexpected