2621 Ridgepoint Drive, Suite 235 Austin, TX 78754

## 800.866.6506 (US)

## www.ikey.com

## **DW-860**

# iKey

## **Small-Footprint Wireless Keyboard**

iKey's DW-860 wireless keyboard combines the compact functionality of a small foo tprint-keyboard with the added convenience of WirelessUSB technology. A 30foot RF range and no line-of-site limitations ensure dynamic applications, including secure communication with a PC inside a metal enclosure. The DW-860 features an integrated HulaPoint II<sup>™</sup> pointing device, mobile mounting holes and a I ightweight polycarbonate case. The DW-860 is ideal for mobility in harsh, rugged environments.



Technical Specifications		
Certifications	NEMA 4X UL60950, FCC Part 15 Class B	
Shock	3x11 ms pulses of 50g on each of 3 axes	
Key Switch	MATERIAL: Industrial silicone rubber LIFE: 10 million cycles TRAVEL: 0.055 in. (1.4mm) ACTUATION FORCE: 7.05 oz +/- 1.06 oz (200g +/- 30g) FEEDBACK: Tactile with mechanical snap	
Vibration	POWER SPECTRAL DENSITY: 0.04g/Hz FREQUENCY RANGE: 20Hz - 2 kHz DURATION OF TEST PER AXIS: 3 hours	
Power	KEYBOARD/HULAPOINT: 3 AA Batteries DONGLE: USB	
Flammability	PRINTED CIRCUIT BOARD: 94 VO SILICONE OVERLAY: 94 HB	
Compatability	KEYBOARD/HULAPOINT: Wireless interface connects to USB Dongle All Windows Operating Systems	
Temperature Range	STORAGE: -40C to +70C (-40F to +158F) OPERATING: -20C to +60C (-4F to +140F)	
Weight	2 lbs +/- 0.10 lbs (0.91 kg +/- 0.05 kg)	
Warranty	1 year limited warranty	
Humidity	100%	
Dimensions	11.39" x 6.31" x 1.87" (w-h-d) 289.6mm x 181.0mm x 47.2mm	
Model Numbers		
Features and Benefits		
<ul> <li>12 Function Keys</li> </ul>	<ul> <li>Integrated HulaPoint II Pointing Device</li> </ul>	

	integrated Halar eint in einting bettee
Manual Binding Key	Small Footprint Design
Up to a 30-foot Range	WirelessUSB Technology (2.4GHz)

©2011 iKey, Ltd. All rights reserved. 2621 Ridgepoint Drive Suite 235 Austin, TX 78754 1-800-866-6506 (US) +1-512-837-0283 (international)