

EX48000 Series

Hardened Web-Smart 5-port 10/100BASE PoE (4 x PoE)
Ethernet Switch



Overview

EtherWAN's EX48000 Series provides a hardened 5-port switching platform supporting IEEE802.3af+ Power over Ethernet, high performance switching with robust management features required for mission-critical and harsh environments where sustained connectivity is crucial.

The EX48000 Series is equipped with four 10/100BASE-TX PoE ports, in combination with one 100FX Fiber option. The IEEE802.3af+ PoE ports provide up to 30W/port with a total power budget of 120W, making the switch truly versatile for connecting with PoE Powered Devices (PD) with different bandwidth and power consumption requirements.

Users are able to access management features such as QoS based on 802.1p, DSCP, and IP precedence. With the hardened specifications, the EX48000 Series is designed to operate at -40°C to 75°C in harsh environments where high ESD, shock and vibration may be present.

EtherWAN — "When Connectivity is Crucial."

Spotlight

• Hardened Grade

- Supports -40°C to 75°C (-40°F to 167°F) operating temperature

• PoE Connectivity

- Port 1 to 4 supports IEEE802.3af+ Power over Ethernet

• Fiber Connectivity

- Up to one 100BASE-FX port with SC or ST option

• Web-Managed Interface

- Comprehensive QoS based on 802.1p, DSCP, and IP precedence

Hardware Specifications

Technology

Standards

- IEEE802.3 10BASE-T
- IEEE802.3u 100BASE-TX/100BASE-FX
- IEEE802.3x Full duplex and flow control
- IEEE802.3af+ Power over Ethernet (PoE)

Forward and Filtering Rate

- 14,880pps for 10Mbps
- 148,810pps for 100Mbps

Packet Buffer Memory

- 512K bits

Processing Type

- Store-and-Forward
- Auto Negotiation
- Half-duplex back-pressure and IEEE802.3x full-duplex flow control
- Auto MDI/MDIX

Address Table Size

- 1024 MAC addresses

Power

Input

- Redundant power inputs:
Terminal Block: 47 - 57VDC
DC Jack: 47 - 57VDC

Power Consumption

- Device: Max. 10W (without PoE)
- PoE power budget (depends on power input): 120W Max.

PoE Power Output

- Port 1 to 4
- IEEE802.3af+: up to 30W/port, 47 - 57VDC, 600mA Max.

Protection

- Reverse polarity protection
- Overload current protection

Mechanical

Casing

- Metal case
- IP30

Dimensions

- 200mm (W) x 134.3mm (D) x 35mm (H)
(7.87" (W) x 5.29" (D) x 1.38" (H))

Weight

- 0.8Kg (1.76lbs.)

Installation

- Desktop, Wall, or DIN-Rail mounting

Interface

Ethernet Ports

- 10/100BASE-TX: 5 or 4 ports
- 100BASE-FX: 0 or 1 ports

LED Indicators

- Per Unit: Power 1 (Green)
Power 2 (Green)
Power 3 (Green)
Fault (Red)
- Per Port: Link/Activity (Green)

Alarm Contact

- One relay output with current 1A @ 250VAC

Environment

Operating Temperature

- -40°C to 75°C (-40°F to 167°F)
Tested @ -40°C to 85°C (-40°F to 185°F)

Storage Temperature

- -40°C to 85°C (-40°F to 185°F)

Ambient Relative Humidity

- 5% to 95% (non-condensing)

Regulatory Approvals

ISO

- Manufactured in an ISO9001 facility

EMI

FCC Part 15B, Class A

EN61000-6-4

EN55022

EN61000-3-2

EN61000-3-3

EMS

EN61000-6-2

- EN61000-4-2 (ESD Standards)
- EN61000-4-3 (Radiated FRI Standards)
- EN61000-4-4 (Burst Standards)
- EN61000-4-5 (Surge Standards)
- EN61000-4-6 (Induced RFI Standards)
- EN61000-4-8 (Magnetic Field Standards)

Environmental Test Compliance

IEC60068-2-6 Fc (Vibration)


IEC60068-2-27 Ea (Shock)

FED STD 101C Method 5007.1 (Free fall w/ package)

Industrial Compliance

NEMA TS2

Dimensions



Ordering Information

Model

EX48050-00B	Hardened Web-smart 5-port 10/100BASE-TX PoE Ethernet Switch
EX48041-X0B	Hardened Web-smart 4-port 10/100BASE-TX + 1-port 100BASE-FX PoE Ethernet Switch

* DIN-Rail mounting kit included

100FX Fiber Options (X)

1	Multi Mode (SC) - 2Km
2	Multi Mode (ST) - 2Km
6	Multi Mode (SC) WDM-TX:1310nm/RX:1550nm - 2Km
7	Multi Mode (SC) WDM-TX:1550nm/RX:1310nm - 2Km
8	Multi Mode (SC) WDM-TX:1310nm/RX:1550nm - 5Km
9	Multi Mode (SC) WDM-TX:1550nm/RX:1310nm - 5Km
A	Single Mode (SC) - 20Km
B	Single Mode (SC) - 40Km
H	Single Mode (ST) - 20Km
P	Single Mode (SC) WDM-TX:1310nm/RX:1550nm - 20Km
Q	Single Mode (SC) WDM-TX:1550nm/RX:1310nm - 20Km
R	Single Mode (SC) WDM-TX:1310nm/RX:1550nm - 40Km
S	Single Mode (SC) WDM-TX:1550nm/RX:1310nm - 40Km

*More 100FX Fiber options also available upon request.

Optional Accessories

KD-AA78000X	DIN-Rail Mounting Kit
SDR-240-48	240W/5A DIN-Rail 48VDC Industrial Power Supply
SDR-480-48	480W/10A DIN-Rail 48VDC Industrial Power Supply