

2621 Ridgepoint Drive, Suite 235 Austin, TX 78754

800.866.6506 (US)

www.ikey.com

FT-86-911-TP

Backlit Keyboard with Integrated Touchpad

The FT-86-911-TP keyboard is designed for vehicle mount in emergency, police, service, transport and marine vessels. With a full-travel keystroke, the FT-86-911-TP feels like a regular keyboard while maintaining the rugged standards of all iKey products. The FT-86-911-TP is now built with laser-etched keys for i mproved backlighting performance. Ideal for in-vehicle use, the FT-86-911-TP features red LED backlit keys for low-light environments, a one-touch emergency key and an integrated touchpad.



Technical Specifications

Certifications UL60950, CE, FCC Part 15, Class B, IP55

Shock 3x11 ms pulses of 50g on each of 3 axes

Cable LENGTH: 4 ft coiled (1.2m) DESIGN: swappable PS/2-Y (providing separate keyboard and mouse connections), or

Single-Cable USB

Key Switch MATERIAL: ABS/Poly-carbonate plastic LIFE: Greater than 10 million cycles TRAVEL: 0.120 in. (3.0mm) ACTUATION

FORCE: 2.2 oz +/- 0.18 oz (62.39g +/- 5g) FEEDBACK: Tactile with mechanical snap

Vibration POWER SPECTRAL DENSITY: 0.04g/Hz FREQUENCY RANGE: 20Hz - 2kHz DURATION OF TEST PER AXIS: 3 hours

Power PS2: KEYBOARD: 315mA@5V (from Keyboard port) TOUCHPAD: 10mA@5V (from Mouse port) USB: 325mA@5V

(from CPU port)

Compatability PS/2 KEYBOARD/TOUCHPAD: All Windows Operating Systems USB KEYBOARD/TOUCHPAD: All Windows and

Macintosh OS

Temperature Range Storage -40C to +90C (-40F to +194F) Operating -40C to +70C (-40F to +158F)

Weight 2.25 lbs +/- 0.10 lbs (1.02 kg +/- 0.05 kg)

Warranty 1 Year Limited Warranty

Humidity 85% Humidity Resistant

Dimensions 11.94― x 7.69― x 1.68― (w-h-d) 303.3mm x 195.3mm x 42.7mm

Model Numbers FT-86-911-TP-PS2: With PS/2 cable FT-86-911-TP-USB: With USB cable

Features and Benefits

12 Function Keys

88-Key Functionality

Integrated Backlighting

Integrated Touchpad

Lightweight ABS Polycarbonate Case

Mobile Mounting Holes

One-Touch Emergency Key