GOT817-834


17" SXGA TFT IP66-rated Stainless Steel Fanless PCT (or Resistive Touch) Panel Computer with Flat Bezel Design $(-20^{\circ}C \sim +55^{\circ}C)$





Features

- 17" SXGA TFT LCD flat bezel-projected capacitive (or resistive) touch
- Water/dust/corrosion-proof design IP66/IP69K (NEMA4X)
- Full stainless steel enclosure with type 316
- Wide operating temperature range of -20°C ~ +55°C
- Fanless system with Intel® Atom™ processor E3827 1.75 GHz
- Wireless network connectivity
- Flexible and expandable with variety of M12 type I/O connections
- Wide range DC 12~36V
- Supports suspension and VESA mount
- M12 type connectors for harsh environments



- 1. Backlight switch
- 2. Brightness adjust
- 3. Power switch (ATX)
- 4. DC power connector (A-coded)
- 5. COM 1 (RS-232/422/485) (A-coded) 6. COM 2 (RS-232/422/485) (A-coded)
- 7. Fthernet (X-coded)
- 8. USB 2.0 x 2 (A-coded)
- 9. USB 2.0 x 2 (A-coded)





















Introduction

The 17-inch GOT817 is specially designed for food processing applications. Its IP66-rating stainless steel housing protects entire system from damage of water, powder and dust. It also outfits wide operating temperature range of -20°C \sim +55°C. Thus, this robust unit is best suited for extreme humility, dusty or wet spaces in food factories or kitchens and more harsh applications.

IP66-sealed system

The GOT817 adopts a water/dust-proof housing design and five IP66-rated connectors. It passes entire system IP66 test by SGS and verified salt mist test.

Full IP66 and IP69K compliance

Full IP66 rating, M12 I/O connectors and IP69K compliance that ensures the product's ability to resist ingress of high temperature and high pressure water and was tested by a spray nozzle with high temperature water (80°C) and a flow rate of 14-16 L/min and a nozzle hold with distance 10-15cm away from the device at angles of 0°, 30°, 60° and 90° for 30 seconds, GOT817 is qualified to meet harsh environment applications.

Wide temp. (-20°C ~ +55°C) & anti-vibration (2G) design

The industrial touch panel PC supports wide temperature of -20°C ~ +55°C. Besides, the patent of anti-vibration for SSD ensures system reliability and stability.

Specifications

-					
Enclosure	Stainless type 316	Stainless type 316			
LCD Panel	Display Type	17" SXGA TFT LCD			
	Brightness (cd/m²)	350 nits			
	Resolution	1280 x 1024			
	Viewing Angle (H/V)	170°/160°			
Main System	CPU	Intel® Atom™ processor E3827 1.75 GHz (Bay Trail)			
	System Memory	1 x 204-pin DDR3L SO-DIMM max. up to 8 GB			
	BIOS	AMI with Axiomtek standard features; such as, SmartView, Ethernet Boot ROM (RPL & PXE), customer CMOS backup			
	Storage	1 x 2.5" SSD 1 x CFast™			
	Watchdog Timer	255 levels, 1~255 sec.			
	Onboard Graphics	Integrated in Intel® GFX			

Specifications

I/O Connector	2 x RS-232/422/485 (default RS-232, A-Coded)
	4 x USB 2.0 (A-Coded)
	1 x 10/100/1000Mbps Ethernet (X-Coded)
Expansion Interface	2 x PCle Mini Card slot
Touchscreen	5-wire resistive touch or projected capacitive multi-touch
Power Supply	Power input 12~36VDC
Dimensions	TBD
Packing Dimensions	TBD
Weight (net/gross)	TBD
Environment	Operating temperature: -20°C ~ +55°C (-4°F ~ +131°F)
	Storage Temperature: -30°C ~ +70°C (-22°F ~ +158°F)
	Relative humidity: 10% ~ 95% @ 40°C, non-condensing
	Operation vibration:
	2G, 5 ~ 500Hz, random for 2.5" SSD
	2G, 5 ~ 500Hz, random for CompactFlash™
Certificate	CE

^{*} W.T.: Wide Temperature. All W.T. supported products have to be sorted by Axiomtek.

Optional Accessories

594B8122100E	Water-proof COM port cable (1.8 m)	_
594B8122820E	Water-proof USB cable (1.8 m)	
594B8152710E	Water-proof LAN cable (1.8 m)	
50964A23000E	72W/24V power adapter with M12 connector	_

Ordering Information

Sunlight readable type	
GOT817-834-C	Flat-bezel design 17" SXGA IP66-rated stainless steel fanless projected capacitive touch panel computer with Intel® Atom™ E3827
GOT817-834-R	Flat-bezel design 17" SXGA IP66-rated stainless steel fanless resistive touch panel computer with Intel® Atom™ E3827

^{*} Specification and certifications are based on options and may vary.

Optional EOS Installation

WES 7			
WE8S			

Optional OS Installation

Windows® 7		
Windows® 8/8.1		



Industrial Panel Computers & Monitors

Overview



Heavy-duty Fanless Touch Panel Computers

Digital Signage Solutions



Healthcare & Medical Solutions







^{*} All specifications and photos are subject to change without notice.