





UX10 FULLY RUGGED TABLET

- 12th Generation Intel[®] Core[™] i5/i7 Processor.
- 10.1" FHD Lumibond display with Getac sunlight readable technology (1,000 nits) and capacitive touchscreen.
- Enhanced enterprise security with optional Intel® vPro®,
 Windows Hello face-authentication camera and multifactor authentication options.
- Versatile I/Os connectivity including Thunderbolt™ 4.
- Enhanced Wi-Fi, GPS and LTE performance.









USB 3.2 Gen 2 Type-A Audio in/out combo





DC in Jack

SPECIFICATIONS

Generation

Operating System Windows 11 Pro

Mobile Computing Platform

Intel® Core™ i5-1235U Processor Max. 4.4GHz with Intel® Turbo Boost Technology - 12MB Intel® Smart Cache

Platform options:

Intel[®] CoreTM i5-1245U vPro[®] Processor Max. 4.4GHz with Intel[®] Turbo Boost Technology - 12MB Intel® Smart Cache

Intel[®] Core™ i7-1255U Processor

Max. 4.7GHz with Intel® Turbo Boost Technology - 12MB Intel® Smart Cache

Intel[®] Core™ i7-1265U vPro[®] Processor Max. 4.8GHz with Intel[®] Turbo Boost Technology - 12MB Intel[®] Smart Cache

Intel® Pentium™ 8505 Processor Max. 4.4GHz with Intel® Turbo Boost Technology - 8MB Intel® Smart Cache

VGA Controller Intel® UHD Graphics

10.1" Wide Viewing Angle TFT LCD WUXGA (1920 x 1200) Protection film 1,000 nits LumiBond display with Getac sunlight readable

technology

Capacitive multi-touch screen

Storage & Memory 8GB DDR4 Optional: 16GB / 32GB DDR4

256GB PCIe NVMe SSD Optional: 512GB / 1TB PCIe NVMe SSD

Keyboard Power button

5 tablet programmable buttons

Pointing Device

Touchscreen - Capacitive multi-touch screen - Optional: Dual mode touchscreen (multi-touch and digitizer)

Expansion Slots

EXPAILSION DIOTS
Optional (top side): 1D/2D imager barcode reader, or Serial port, or USB 3.2 Gen 1 Type-A port, or LAN port (RJ45) , or microSD or HF RFID reader ', or HDMI 2.0."
Optional (right side): LAN port (RJ45) or Fingerprint reader "

Optional (back side): Smart card reader, or Bridge battery, or Bridge battery + Smart card reader

I/O Interface

I/O Interface

HD webcam x 1 '

8M pixels auto focus rear camera x 1

Audio in/out combo x 1

DC in Jack x 1

USB 3.2 Gen 2 Type-A x 1

Docking connector x 1

Thunderbolt M 4 Type-C x 1

Optional: Windows Hello face-authentication camera

(front-facing) x 1 '

्राप्ताचार अभारावण्ड तथाठ race-authentication camera (front-facing) x 1 ^v Optional: RF antenna pass-through for GPS, WWAN and WLAN

Communication Interface Optional: 10/100/1000 base-T Ethernet Intel® Wi-Fi 6E AX211, 802.11ax Bluetooth (v5.3) ^w

Optional: 4G LTE mobile broadband with integrated GPS vii.

Optional: 5G Sub-6 with integrated GPS vii, viii, ix Dual SIM (Micro-SIM 3FF and e-SIM) vii, viii

Security Features

TPM 2.0
Kensington lock
Optional: Intel® vPro® Technology
Optional: HF RFID reader III

Optional: Finderprint reader
Optional: Smart card reader
Optional: Smart card reader
Optional: Windows Hello face-authentication camera

(front-facing) '

Power
AC adapter (65W, 100-240VAC, 50/60 Hz)
Li-ion battery (11.1V, typical 4200mAh; min. 4080mAh) x 1
Optional: High capacity Li-ion battery (10.8V, 9240mAh) x 1
Optional: Bridge battery

Dimension (W x D x H) & Weight

279 x 194.5 x 23.5mm (10.98" x 7.65" x 0.92") x 1.22kg (2.68lbs) x 1

Rugged Feature MIL-STD-810H certified IP66 certified
MIL-STD-461G certified xii

Vibration & 6ft (1.8m) drop resistant xiii Optional: ANSI/UL 121201, CSA C22.2 NO. 213 (Class I, Division 2, Groups A, B, C, D) xiv

Environmental Specification

Temperature **:
- Operating: -29°C to 63°C / -20°F to 145°F
- Storage: -51°C to 71°C / -60°F to 160°F
- Humidfty:
- 95% RH, non-condensing

Pre-installed Software

Getac Utility
Getac Camera
Getac Geolocation
Getac Barcode Manager
Getac Driving Safety Utility (trial version)
Getac KeyWedge Barcode Reader Utility (trial version)
Optional: Absolute Persistence®

Getac Driving Safety Utility Getac KeyWedge Barcode Reader Utility Getac Device Monitoring System (GDMS) Getac VGPS Utility xvii

Accessories

Battery (11.1V, typical 4200mAh; min. 4080mAh) AC adapter (65W, 100-240VAC) Capacitive stylus with tether

Optional: Carry bag Folio case

Folio case
Battery (11.1V, typical 4200mAh; min. 4080mAh)
High capacity Li-ion battery (10.8V, 9240 mAh)
Multi-Bay charger (Dual-Bay)
Multi-Bay charger (Eight-Bay)
AC adapter (65W, 100-240VAC)
AC adapter (90W, 100-240VAC)
MIL-STD-461 AC adapter (90W, 100-240VAC)
DC-DC vehicle adapter (120W, 11-32VDC)
Digitizer pen
Capacitive stylus with tether
Protection film
Hard handle

Protection TIIM
Hard handle
Rotating hand strap with kickstand
Shoulder strap (2-point)
Shoulder harness (4-point; handsfree)
Detachable keyboard

Vehicle cradle *
Keyboard dock Vehicle dock xviii Office dock 100W Type-C adapter

Office Dock Serial Port 1 1 External VGA 1 Microphone 1 Audio Output 1 1 1 DC in Jack USB 2.0 x 2 USB 3.2 Gen 1 x 2 USB 2.0 x 2 USB 3.2 Gen 1 x 2 1 IAN 1 HDMI 1.4 1 RF Antenna Connector 3 (WWAN, WLAN, GPS) 1 Kensington Lock 1

Vehicle Dock

UX10 FULLY RUGGED TABLET

Bumper-to-Bumper warranty
Accidents can take your equipment out of service when you least expect it, especially in a rugged environment, which can cause costly equipment downtime.
That is why Getac has introduced accidental damage as standard under our Bumper-to-Bumper warranty, to help minimize your enterprise IT costs.
Bumper-to-Bumper is your hassle-free guarantee. That means you can depend on us to have your unit back in service within days.

Standard

3 years Bumper-to-Bumper

- 13.56MHz contactless HF RFID reader (ISO 15693, 14443 A/B, Mifare and FeliCa™ compliant).
 1D/2D imager barcode reader, Serial port, USB 3.2 Gen 1 Type-A port, LAN port (R/A5), HF RFID reader, MicroSD and HDMI 2.0 are mutually exclusive options.
 Fingerprint reader and LAN Port are mutually exclusive options.
 Smart card reader, Bridge battery and Bridge battery + Smart card reader are mutually exclusive options.
 FHD webcam and optional Windows Hello face-authentication camera (front-facing) are mutually exclusive options.

- authentication camera (inforcacing) are inactions exclusive options. Bluetooth performance and connectable distance may be subject to interference with the environments and performance on client devices, users may be able to reduce effects of interference by minimizing the number of active Bluetooth wireless devices that is operating in

- On active Biotech Whiteless devices that is operating in the area.

 One physical SIM card slot and one eSIM.

 Network service may vary depending on local telecommunication providers.

 Supports GPS, GLONASS, Galileo, BeiDou and QZSS. Only available in US, UK, EU, Australia and New Zealand.

 Units with 4G LTE option come with an embedded SIM card slot.

 Weight and dimensions vary from configurations and optional accessories.

 MIL-STD-461 90W AC adapter sold separately.

 Drop test results vary from configurations and optional accessories.

- XIV.
- Available with limited configurations and environment Conditions.
 Tested by an independent third-party test lab following MIL-STD-810H. conditions. XV.
- IVIIL-51D-810H.
 Available when barcode reader option is selected.
 Models require either embedded or standalone GPS
- module.

 Gamber Johnson and Havis vehicle docks are e-mark X\/III

Information provided herewith is for reference only, available specification shall be subjected to quotation by request.



Fieldworks Direct B.V. Veemarktkade 8 NL-5222 AE Den Bosch

+31 (0) 73 624 1111 E info@fieldworks.nl www.fieldworks.nl





5F, Building A, No. 209, Section 1, Nangang Rd., Nangang Dist., Taipei City, 115018, Taiwan, R.O.C. Tel: +886 2 2785 7888 globalmarketing@getac.com l

www.getac.com Copyright © 2023 Getac Technology Corporation and/or any of its affiliates. All Rights Reserved. Information provided herewith is for reference only, available specification shall be subjected to quotation by request.