



IK-18-USB

MOBILE NUMERIC PAD - NEW!

- · ABS polycarbonate
- Standard VESA mounting bracket, mobile mountable
- PS2 or USB connection
- Black
- · Built to IP 65 standards (water-resistant)
- Backlit (green)

Product Code IK-18-USB

| CERTIFICATIONS | IP65 |
|-------------------|---|
| SHOCK | 3 X 11 ms pulses of 50g on each of 3 axis |
| KEY SWITCH | MATERIAL: Industrial Silicone Rubber |
| | LIFE: Greater Than 10 Million Cycles |
| | TRAVEL: 0.055 in. |
| | ACTUATION FORCE: 7.05 oz. +/- 1.06oz (200g +/- 30g) |
| | FEEDBACK: Tactile with Mechanical Snap |
| VIBRATION | POWER SPECTRAL DENSITY: .04g²/HZ |
| | FREQUENCY RANGE: 20Hz-2Khz |
| | DURATION OF TEST PER AXIS: 3 hours |
| POWER | PS2: 175mA@5V (from Keyboard port) |
| | USB: 175mA@5V (from USB port) |
| TEMPERATURE RANGE | STORAGE: -40°F to +194°F (-40°C to +90°C) |
| | OPERATING: -40°F to +158°F (-40°C to +70°C) |
| WEIGHT | 0.36 lbs +/- 0.10 lbs |
| WARRANTY | 1 Year Limited Warranty |
| HUMIDITY | 100% Humidity Resistant |
| DIMENSIONS | 3.974" x 5.219" x .850" |
| MODEL NUMBERS | IK-18-USB |