

2621 Ridgepoint Drive, Suite 235 Austin, TX 78754

800.866.6506 (US)

www.ikey.com

KYB-81-OEM

Compact Industrial OEM Keyboard

The KYB-81-OEM provides full 101-key functionality in a small-footprint size. Its compact design and durable construction ensure mobility and durability no matter the application. The numeric keypad is integrated onto the alpha keys and is easily accessed by pressing the function and NumLock keys. Each kit is comprised of an industrial silicone keypad, switch matrix board, keyboard controller and cables.



Technical Specifications

Certifications NEMA 4X UL60950, FCC Part 15 Class B

Shock 3x11 ms pulses of 50g on each of 3 axes

Cable LENGTH: 10 feet (3 meters) DESIGN: "Y" PS/2, AT or Single-Cable USB

Key Switch MATERIAL: Industrial silicone rubber LIFE: 10 million cycles TRAVEL: 0.055 ACTUATION FORCE: 180g (+/- 30g)

FEEDBACK: Tactile with mechanical snap

Vibration POWER SPECTRAL DENSITY: 0.04g/Hz FREQUENCY RANGE: 20Hz - 2 kHz DURATION OF TEST PER AXIS: 3

hours

Power KEYBOARD: 5mA @ 5V (from keyboard port) USB: 50mA @ 5V (from CPU port)

Flammability PRINTED CIRCUIT BOARD: 94 VO SILICONE OVERLAY: 94 HB INTERFACE CABLE: 94 VO

Compatability PS/2: All Windows Operating Systems USB: All Windows and Macintosh OS

Temperature Range STORAGE: -40C to +90C OPERATING: -40C to +70C

Weight 1.5 lbs (0.68 kg)

Warranty 90 day limited warranty

Humidity 100% (when properly installed)

Dimensions 11.35" x 5.11" x 0.42" (w-h-d) 288.3mm x 129.8mm x 10.7mm

Model Numbers

Features and Benefits

• 12 Function Keys
• 81-Key Functionality

OEM Kit: PCB, rubber overlay, and cable
 USB, PS/2 and AT Configurations Available

©2011 iKey, Ltd. All rights reserved. 2621 Ridgepoint Drive Suite 235 Austin, TX 78754 1-800-866-6506 (US) +1-512-837-0283 (international)