

2621 Ridgepoint Drive, Suite 235 Austin, TX 78754

800.866.6506 (US)

www.ikey.com

PM-72

Panel Mount Keyboard with Oversized Keys

iKey's innovative PM-72 panel mount keyboard was designed to accommodate rugged applications in manufacturing, material handling and remote data entry. Its unique, oversize keys are color arranged and feature a roomy layout for convenient gloved-hand use. It features a small-footprint design and a large numeric pad. Like other keyboards in the iKey line, the PM-72 is constructed with an industrial silicone keypad, sealing it from dust, liquids and corrosives.



Technical Specifications

Certifications NEMA 4X UL60950, FCC Part 15 Class B

Shock 3x11 ms pulses of 50g on each of 3 axes

Cable LENGTH: 4 ft coiled (1.2m) DESIGN: PS/2 or USB Cable

Key Switch MATERIAL: Industrial Silicone Rubber LIFE: Greater than 10 Million Cycles TRAVEL: 0.055 in. (1.4mm) ACTUATION

FORCE: 4.74 oz. +/- 0.70 oz. (135g +/- 20g) FEEDBACK: Tactile with Mechanical Snap

Vibration POWER SPECTRAL DENSITY: 0.04g/Hz FREQUENCY RANGE: 20Hz - 2 kHz DURATION OF TEST PER AXIS: 3

hours

Power PS/2: KEYBOARD: 50mA@5V (from Keyboard port) USB: 50mA@5V (from CPU port)

Compatability PS/2 KEYBOARD: All Windows Operating Systems USB KEYBOARD: All Windows and Macintosh OS

Temperature Range STORAGE: -40C to +90C (-40F to +194F) OPERATING: -40C to +70C (-40F to +158F)

Weight 1.75 lbs +/- 0.10 lbs (0.80 kg +/- 0.05 kg)

Warranty 1 year limited warranty

Humidity 100%

Dimensions 11.80" x 6.79" x 1.36" (w-h-d) 299.7mm x 172.5mm x 34.5mm

Model Numbers

Features and Benefits

• 72-Key Functionality • 8 Function Keys

• USB and PS/2 configurations available

©2011 iKey, Ltd. All rights reserved. 2621 Ridgepoint Drive Suite 235 Austin, TX 78754 1-800-866-6506 (US) +1-512-837-0283 (international)