



## PM-860

### COMPACT SIZE WITH INTEGRATED HULAPOINT II™

The small footprint PM-860 is built for versatility and convenience. It features 84-key functionality and an integrated HulaPoint II™, an upgraded pointing device that offers improved sensitivity and increased durability. Constructed with a sealed industrial silicone keypad and designed to meet NEMA 4X specifications, the PM-860 is ideal for mobile applications and space saving. In addition, its integrated HulaPoint II™ pointing device eliminates the need for an external mouse. iKey's rugged panel mount keyboards allow for easy integration into workstations or other industrial environments.

- Features:
- 12 Function Keys
  - 84-Key Functionality
  - ABS Polycarbonate Frame
  - Integrated HulaPoint II™ Pointing Device
  - USB and PS/2 configurations available



### Product Code PM-860

CERTIFICATIONS	NEMA 4X UL60950, FCC Part 15 Class B
SHOCK	3x11 ms pulses of 50g on each of 3 axes
CABLE	LENGTH: 10 feet (3 meters) DESIGN: "Y" PS/2 (providing separate keyboard and mouse connections), or Single-Cable USB
KEY SWITCH	MATERIAL: Industrial Silicone Rubber LIFE: Greater than 10 Million Cycles TRAVEL: 0.055 in. (1.4mm) ACTUATION FORCE: 7.05 oz. +/- 1.06 oz. (200g +/- 30g) FEEDBACK: Tactile with Mechanical Snap
VIBRATION	POWER SPECTRAL DENSITY: 0.04g/Hz FREQUENCY RANGE: 20Hz - 2 kHz DURATION OF TEST PER AXIS: 3 hours
POWER	KEYBOARD: 50mA@5V (from CPU port) HULAPOINT: 35mA@ 5V (from Mouse port) USB: 85mA@5V (from CPU port)
COMPATIBILITY	PS/2 KEYBOARD/HULAPOINT: All Windows Operating Systems USB KEYBOARD/HULAPOINT: All Windows and Macintosh OS
TEMPERATURE RANGE	STORAGE: -40C to +70C (-40F to +158F) OPERATING: -20C to +60C (-4F to +140F)
WEIGHT	1.75 lbs +/- 0.10 lbs (0.79 kg +/- 0.05kg)
WARRANTY	1 year limited warranty
HUMIDITY	100% (when properly installed)
DIMENSIONS	11.80" x 6.79" x 1.35" (w-h-d) 299.7mm x 172.5mm x 34.3mm CUTPIT: 10.40" x 5.40" (w-h) 264.2mm x 137.2mm
MODEL NUMBERS	PM-860-PS2: With PS/2 cable PM-860-USB: With USB cable