2621 Ridgepoint Drive, Suite 235 Austin, TX 78754

800.866.6506 (US)

www.ikey.com

SL-18-OEM

OEM Backlit Numeric Pad

iKey

The SL-18-OEM is an 18-key OEM numeric keypad that is designed for easy i ntegration into any system. The SL-18-OEM has integrated green LED b acklighting, and is available with customizable LED color options. When properly installed, the SL-18-OEM is NEMA 4X-compliant and resistant to dirt, debris and I iquids.



Technical Specifications		
Certifications	NEMA 4X (when properly installed) UL60950, FCC Part 15 Class B	
Shock	3x11 ms pulses on each of 3 axes	
Key Switch	MATERIAL: Industrial silicone rubber LIFE: Greater than 10 million cycles TRAVEL: 0.055 in. ACTUATION FORCE: 7.05 oz. (200g) FEEDBACK: Tactile with mechanical snap	
Vibration	POWER SPECTRAL DENSITY: .04g2/HZ FREQUENCY RANGE: 20Hz-2Khz DURATION OF TEST PER AXIS: 3 hours	
Power	PS2: 175mA@5V (from keyboard port) USB: 175mA@5V (from USB port)	
Flammability	PRINTED CIRCUIT BOARD: 94 VO SILICONE OVERLAY: 94 HB INTERFACE: 94 VO	
Compatability	PS2 NUMERIC PAD: All Windows OS USB NUMERIC PAD: All Windows and Macintosh OS	
Temperature Range	STORAGE: -40C to +90C OPERATING: -40C to +70C	
Weight	0.20 lbs (0.09 kg)	
Warranty	90 day limited warranty	
Humidity	100%	
Dimensions	3.505" x 4.735" x 0.300" (w-h-d) 89.03mm x 120.27mm x 7.62mm	
Model Numbers	SL-18-OEM-USB: With USB cable SL-18-OEM-PS2: With PS/2 cable	
Features and Benefits		

 Integrated Backlighting 	Meets NEMA 4X (IP65) Specifications
Small Footprint Design	

©2011 iKey, Ltd. All rights reserved. 2621 Ridgepoint Drive Suite 235 Austin, TX 78754 1-800-866-6506 (US) +1-512-837-0283 (international)