

SL-75-OEM

OEM Compact Keyboard

The compact SL-75-OEM is excellent for integration into industrial and mobile applications. This rugged keyboard is designed to meet NEMA 4X specifications when properly installed. The SL-75-OEM kit includes an industrial silicone rubber pad, board and cable. The SL-75-OEM features red LED backlit keys for use in a reas with minimal lighting and 75 keys, including 12 function keys.



Technical Specifications

Certifications	NEMA 4X, CE UL60950, FCC Part 15 Class B
Shock	3 x 11 ms pulses of 50g on each of 3 axis
Cable	LENGTH: 10 feet straight (3 m)
Key Switch	MATERIAL: Industrial Silicone Rubber LIFE: Greater than 10 million cycles TRAVEL: 0.055 in. ACTUATION FORCE: 4.76 oz. (135g) FEEDBACK: Tactile with Mechanical Snap
Vibration	POWER SPECTRAL DENSITY: .04g/HZ FREQUENCY RANGE: 20Hz-2Khz DURATION OF TEST PER AXIS: 3 hours
Power	PS/2: 200mA@5V (from Keyboard port) USB: 200mA@5V (from CPU port)
Compatability	PS/2: All Windows Operating Systems USB: All Windows and Macintosh OS
Temperature Range	STORAGE: -40C to +90C OPERATING: -40C to +70C
Weight	.75 lbs (0.34 kg)
Warranty	90 Day Limited Warranty
Humidity	100% Humidity Resistant (when properly installed)
Dimensions	7.85" x 3.85" x 0.36" (w-h-d) 199.4 x 97.8 x 9.1 mm
Model Numbers	SL-75-OEM-PS2: With PS/2 Cable SL-75-OEM-USB: With USB Cable SL-75-OEM-STD: With AT/Serial Cable

Features and Benefits

- Red Backlit Keys
- USB, PS/2 and AT/serial configurations available