

2621 Ridgepoint Drive, Suite 235 Austin, TX 78754

800.866.6506 (US)

www.ikey.com

## **SLK-101-8L-OEM**

## Rugged OEM Keyboard Offers Eight Levels of Backlightling

iKey's SlimKey™ SLK-101-8L-OEM provides full-sized versatility in a rugged, c ompact design. It features eight levels of green LED backlighting, and is also available in a night vision (NVIS) compatible configuration. Engineered for NEMA 4X protection from dust, water and corrosive liquids, the SLK-101-8L is ideal for use in military applications. The large numeric pad on the SLK-101-8L allows for easy data entry, while the robust polycarbonate case stands up in the roughest of conditions. Ideal for harsh EMI environments, this rugged keyboard is designed to meet MIL-STD-461 specifications.Each kit is comprised of an industrial silicone keypad, switch matrix board, keyboard controller and cables.



## **Technical Specifications**

Shock 3x11 ms pulses of 50g on each of 3 axes

Key Switch MATERIAL: Industrial silicone rubber LIFE: 10 million cycles TRAVEL: 0.055 in. (1.4mm) ACTUATION FORCE: 7.05 oz

+/- 1.06 oz (200g +/- 30g) FEEDBACK: Tactile with mechanical snap

Vibration POWER SPECTRAL DENSITY: 0.04g/Hz FREQUENCY RANGE: 20Hz - 2 kHz DURATION OF TEST PER AXIS: 3 hours

Power USB: 50mA@5V (from CPU port)

Compatability STORAGE: -40C to +90C (-40F to +194F) OPERATING: -40C to +70C (-40F to +158F)

Weight 1.00 lbs +/- 0.10 lbs (0.45 kg +/- 0.05 kg)

Warranty 1 year limited warranty

Humidity 100%

Dimensions 14.40" x 5.05" x 0.25" (w-h-d) 365.7mm x 128mm x 6.4mm

## **Features and Benefits**

Green Backlit Keys

• Integrated 10-Key Numeric Pad

· OEM Kit: PCB, rubber overlay, and cable

Green LED

Thin Design

Industrial Silicone Rubber Keypad

• NVIS Compliant -Green B backlighting

• USB

• Silicone Rubber

High EMI Standards

Designed to meet MIL-STD-461E Specifications