

2621 Ridgepoint Drive, Suite 235 Austin, TX 78754

800.866.6506 (US)

www.ikey.com

SLK-101-M

Backlit Mobile Industrial Keyboard

iKey's SlimKey™ SLK-101-M keyboard provides full-size versatility in a rugged, c ompact design. It features red LED backlit keys for use in areas with minimal lighting. Engineered for NEMA 4X protection from dust, water and corrosive liquids, the SlimKey™ SLK-101-M is ideal for use in industrial, medical and material h andling applications. Its large numeric pads allow for easy data entry, while its ro bust polycarbonate cases have built-in mounting holes for convenient vehicle use.



Technical Specifications

Certifications NEMA 4X UL60950, FCC Part 15 Class B

Shock 3x11 ms pulses of 50g on each of 3 axes

Cable LENGTH: 10' straight (3 m)

Key Switch MATERIAL: Industrial silicone rubber LIFE: 10 million cycles TRAVEL: 0.055 in. (1.4mm) ACTUATION FORCE: 7.05

oz. +/- 1.06 oz. (200g +/- 30g) FEEDBACK: Tactile with mechanical snap

Vibration POWER SPECTRAL DENSITY: 0.04g/Hz FREQUENCY RANGE: 20Hz - 2 kHz DURATION OF TEST PER AXIS: 3

hours

Power PS/2: 210mA@5V (from Keyboard port) USB: 210mA@5V (from CPU port)

Flammability PRINTED CIRCUIT BOARD: 94 VO SILICONE OVERLAY: 94HB

Compatability PS/2: All Windows Operating Systems USB: All Windows and Macintosh OS

Temperature Range STORAGE: -40C to +90C (-40F to +194F) OPERATING: -40C to +70C (-40F to +158F)

Weight 2 lbs +/- 0.10 lbs (0.91 kg +/- 0.05 kg)

Warranty 1 year limited warranty

Humidity 100%

Dimensions 14.74" x 5.69" x 1.61" (w-h-d) 374.4mm x 144.5mm x 40.9mm

Features and Benefits

10-Key Numeric Pad
12 Function Keys

Built-In Mounting Holes
Integrated Backlighting

MS Windows Function Keys
USB and PS/2 configurations available

©2011 iKey, Ltd. All rights reserved. 2621 Ridgepoint Drive Suite 235 Austin, TX 78754 1-800-866-6506 (US) +1-512-837-0283 (international)