

2621 Ridgepoint Drive, Suite 235 Austin, TX 78754


800.866.6506 (US)

www.ikey.com

SLK-101C

Backlit Industrial Keyboard with QuickLock™

iKey's SlimKey™ SLK-101C keyboard provides full-sized versatility in a rugged, c ompact design. Designed for easy cleaning, the SLK-101C features an integrated "QuickLock™" to disable the keyboard funtions during cleaning procedures. It also fe atures green LED backlit keys for use in areas with minimal lighting.





Technical Specifications

Certifications NEMA 4X UL60950, FCC Part 15 Class B

Shock 3x11 ms pulses of 50g on each of 3 axes

Cable LENGTH: 10' straight USB (3 m)

Key Switch MATERIAL: Industrial silicone rubber LIFE: 10 million cycles TRAVEL: 0.055 in. (1.4mm) ACTUATION FORCE: 7.05

oz. +/- 1.06 oz. (200g +/- 30g) FEEDBACK: Tactile with mechanical snap

Vibration POWER SPECTRAL DENSITY: 0.04g/Hz FREQUENCY RANGE: 20Hz - 2 kHz DURATION OF TEST PER AXIS: 3

hours

Power USB: 210mA@5V (from CPU port)

Flammability PRINTED CIRCUIT BOARD: 94 VO SILICONE OVERLAY: 94 HB INTERFACE CABLE: 94 VO

Compatability USB: All Windows and Macintosh OS

Temperature Range STORAGE: -40C to +90C (-40F to +194F) OPERATING: -40C to +70C (-40F to +158F)

Weight 1.5 lbs +/- 0.10 lbs (0.68 kg +/- 0.05 kg)

Warranty 1 year limited warranty

Humidity 100%

Dimensions 14.60" x 5.55" x 0.92" (w-h-d) 370.8mm x 141mm x 23.4mm

Model Numbers

Features and Benefits

10-Key Numeric Pad
12 Function Keys

• Slim, Compact Design • USB configurations available

QuickLock™