

SLK-102-461

Designed to meet MIL-STD-461 standards

Designed to meet MIL-STD-461 standards, iKey's SlimKey® SLK-102-461 is ideal for harsh environments where electromagnetic interference is a top concern. In addition the SLK-102-461 provides full-size versatility in a rugged, compact design, with the added convenience of an integrated HulaPoint II®. The SlimKey® SLK-102-461 is engineered to meet NEMA 4X specifications, and is resistant to sand, debris and the elements. The large numeric pad on the SLK-102-461 allows for easy data entry, while the robust polycarbonate case is durable in the roughest of environments. Other features also include red LED backlit keys for nighttime use.



Technical Specifications

Certifications	NEMA 4X UL60950, FCC Part 15 Class B
Shock	3 x 11 ms pulses of 50g on each of 3 axes
Key Switch	MATERIAL: Industrial Silicone Rubber LIFE: Greater Than 10 Million Cycles TRAVEL: 0.055 in. (1.4mm) ACTUATION FORCE: 7.05 oz. +/- 1.06oz (200g +/- 30g) FEEDBACK: Tactile with Mechanical Snap
Vibration	POWER SPECTRAL DENSITY: .04G/hz FREQUENCY RANGE: 20Hz-2Khz DURATION OF TEST PER AXIS: 3 hours
Compatibility	Ps/2 KEYBOARD/HULAPOINT: All Windows Operating Systems
Temperature Range	STORAGE: -40F to 194F (-40C to +90C) OPERATING: -40F to +158F (-40C to +70C)
Weight	1.5 lbs +/- 0.10 lbs (0.68 kg +/- 0.05 kg)
Warranty	1 year warranty
Dimensions	5.55" x 14.60" x 1.05" (w-h-d) 141mm x 370.9mm x 26.7mm

Features and Benefits

- 12 Function Keys
- Military
- Integrated HulaPointII Pointing Device
- Designed to meet MIL-STD-461F Specifications
- Full-Size