

2621 Ridgepoint Drive, Suite 235 Austin, TX 78754

800.866.6506 (US)

www.ikey.com

## **SLK-77**

## **Compact Backlit Industrial Keyboard**

The compact SLK-77 keyboard is packed with functionality. It features a full QWERTY keyboard layout, 12 function keys, and red LED backlighting in a rugged ABS polycarbonate case measuring 9.27" x 3.87" (width-height). The SLK-77 is designed to meet NEMA 4X specifications, with a completely sealed industrial silicone rubber keypad that can withstand the dirt, dust, water and corrosives that often exist in harsh environments. It is an excellent keyboard for material handling, mobile and industrial applications.



## **Technical Specifications**

Certifications NEMA 4X, CE UL60950, FCC PART 15 CLASS B

Shock 3 x 11 ms pulses of 50g on each of 3 axes

Cable LENGTH: 3' straight (0.91 m) DESIGN: Single Cable USB

Key Switch MATERIAL: Industrial Silicone Rubber LIFE: Greater than 10 Million Cycles TRAVEL: 0.055 in. (1.4mm) ACTUATION

FORCE: 4.76 oz. +/- 1.06 oz. (135g +/- 30g) FEEDBACK: Tactile with Mechanical Snap

Vibration POWER SPECTRAL DENSITY: .04g/HZ FREQUENCY RANGE: 20Hz - 2Khz DURATION OF TEST PER AXIS: 3 hours

Power USB: 200mA@5V (from CPU port)

Compatability USB: All Windows and Macintosh OS

Temperature Range STORAGE: -40C to +90C (-40F to +194F) OPERATING: -40C to +70C (-40F to +158F)

Weight 1.00 lbs +/- 0.10 lbs (0.45 kg +/- 0.05 kg)

Warranty 1 year limited warranty

Humidity 100% Humidity Resistant

Dimensions 9.27" x 3.87" x 0.90" (w-h-d) 235.5mm x 98.3mm x 22.9mm

Model Numbers SLK-77-USB

## **Features and Benefits**

Industrial Silicone Rubber Keypad

Red Backlit Keys

Ultra-Small Footprint Design

• USB configurations available