

2621 Ridgepoint Drive, Suite 235 Austin, TX 78754

# iKey

## 800.866.6506 (US)

www.ikey.com

## SLK-880-FSR-OEM

## Military Keyboard with Adjustable Backlighting

The SLK-880-FSR-OEM exceeds NEMA 4X requirements when properly installed and is fully-submersible, meeting IP68 specifications. Unique features of the SLK-880-FSR-OEM include a conductive plastic case, adjustable green backlighting that is also available in a night vision (NVIS) compatible configuration, and an integrated Interlink Electronics Force Sensing Resistor (FSR) pointing device.



Technical Specifications	
Certifications	UL60950
Shock	3 X 11 ms pulses of 50g on each of 3 axis
Cable	6 ft. straight (1.8 m)
Key Switch	MATERIAL: Industrial Silicone Rubber LIFE: Greater Than 10 Million Cycles TRAVEL: 0.055 in. ACTUATION FORCE: 6.35 oz. +/- 0.71 oz (180g +/- 20g) FEEDBACK: Tactile with Mechanical Snap
Vibration	POWER SPECTRAL DENSITY: .04g/HZ FREQUENCY RANGE: 20Hz-2Khz DURATION OF TEST PER AXIS: 3 hours
Power	USB: 300mA@5V (from CPU port)
Compatability	USB: All Windows and Macintosh OS
Temperature Range	STORAGE: -40F to +167F (-40C to +75C) OPERATING: -40F to +158F (-40C to +70C)
Weight	1.75 lbs +/- 0.10 lbs (0.79 kg +/- 0.05 kg)
Warranty	1 Year Limited
Humidity	100% Humidity Resistant
Dimensions	11.23" x 6.62" x 0.17" (w-h-d) 285.2mm x 168.1mm x 4.3 mm
Model Numbers	SL-880-FSR-OEM-USB: With USB Cable
Features and Benefits	

Adjustable backlighting

• Integrated FSR pointing device

Optional NVIS Compliant - Green B backlighting

©2011 iKey, Ltd. All rights reserved. 2621 Ridgepoint Drive Suite 235 Austin, TX 78754 1-800-866-6506 (US) +1-512-837-0283 (international)